



 **alsident[®]
system**

– a cleaner working environment

ALUMINIUM SYSTEM 50 + 75 + 100

AIR VOLUME AND REACH

SYSTEM 50

Air volume: 45 – 85 m³/h
Max. reach: 1660 mm

SYSTEM 75

Air volume: 80 – 180 m³/h
Max reach: 1990 mm

SYSTEM 100

Air volume: 140 – 400 m³/h
Max reach: 2630 mm



PP – CHEMICAL RESISTANT SYSTEM 63 + 75 + 100



AIR VOLUME AND REACH

SYSTEM 63

Air volume: 60-120 m³/h
Max reach: 1550 mm

SYSTEM 75

Air volume: 80 – 180 m³/h
Max reach: 1990 mm

SYSTEM 100

Air volume: 140 – 400 m³/h
Max reach: 2630 mm

ANTISTATIC ESD/EX SYSTEM 50 + 75 + 100



EX II 1 GD



STANDARDS ESD & EX

SYSTEM 50

ESD: IEC 61340-5-1

SYSTEM 75

ESD: IEC 61340-5-1
IEC 61340-4-1
EX: EN 13463-1:2001
IEC 61340-4-1:2003

SYSTEM 100

ESD: IEC 61340-5-1
IEC 61340-4-1
EX: EN 13463-1:2001
IEC 61340-4-1:2003

WORK CABINETS SYSTEM 25



AIR VOLUME & SIZE

SYSTEM 25

Air volume: 117 – 850 m³/h

L x B [mm]:

Type 1: 1000 x 600

Type 2: 635 x 480

Type 3: 420 x 320

TYPE 2



TYPE 3



FLEX SYSTEM 50 AL & AS TELESCOPIC SYSTEM 75 AL

AIRFLOW ALARM SYSTEM 10

AIR VOLUME AND REACH

FLEX – SYSTEM 50

Air volume: 45-85 m³/h

Max. reach: 900 mm

TELESCOPIC – SYSTEM 75

Air volume: 80-180 m³/h

Max reach: 1900 mm



STANDARDS

SYSTEM 50 FLEX

ESD: IEC 61340-5-1



Airflow < 4 m/sek:

