

ALUMINIUM SYSTEM 50 + 75 + 100

PP – CHEMICAL RESISTANT SYSTEM 63 + 75 + 100

FLEX SYSTEM 50 AL & AS TELESCOPIC SYSTEM 75 AL

AIRFLOW ALARM SYSTEM 10



AIR VOLUME AND REACH

SYSTEM 50

Air volume: 45 – 85 m³/h
Max. reach: 1660 mm

SYSTEM 75

Air volume: 80 – 180 m³/h
Max reach: 1990 mm

SYSTEM 100

Air volume: 140 – 400 m³/h
Max reach: 2630 mm



AIR VOLUME AND REACH

SYSTEM 63

Air volume: 60-120 m³/h
Max reach: 1550 mm

SYSTEM 75

Air volume: 80 – 180 m³/h
Max reach: 1990 mm

SYSTEM 100

Air volume: 140 – 400 m³/h
Max reach: 2630 mm



AIR VOLUME AND REACH

FLEX – SYSTEM 50

Air volume: 45-85 m³/h
Max. reach: 900 mm

TELESCOPIC – SYSTEM 75

Air volume: 80-180 m³/h
Max reach: 1900 mm

STANDARDS

SYSTEM 50 FLEX

ESD: IEC 61340-5-1



Airflow < 4 m/sek:



ANTISTATIC ESD/EX SYSTEM 50 + 75 + 100

WORK CABINETS SYSTEM 25



STANDARDS ESD & EX

SYSTEM 50	SYSTEM 75	SYSTEM 100
ESD: IEC 61340-5-1	ESD: IEC 61340-5-1 IEC 61340-4-1	ESD: IEC 61340-5-1 IEC 61340-4-1
	EX: EN 13463-1:2001 IEC 61340-4-1:2003	EX: EN 13463-1:2001 IEC 61340-4-1:2003



AIR VOLUME & SIZE
SYSTEM 25
 Air volume: 117 – 850 m³/h
 L x B [mm]:
 Type 1: 1000 x 600
 Type 2: 635 x 480
 Type 3: 420 x 320

